

Trailer Life

2001 TOWING GUIDE

This year's Towing Guide is the biggest ever, surpassing last year's listing by nearly two-fold. It's hard to believe, but manufacturers have yet to run out of ideas for new models and technology to stuff into these rugged vehicles, and there doesn't appear to be an end in sight. To keep the 2001 Tow Ratings from growing larger than the national debt, we've excluded any vehicles that can tow less than 2000 pounds. And while every effort has been made to ensure the accuracy of all ratings, keep in mind that much of the information we receive is preliminary, and may have changed slightly by the time you visit your dealer's showroom. When in doubt, consult the manufacturer's towing guide, available at your dealership -- it's the final word.

Compiled by Chris Hemer

RVING AT ITS BEST

ACURA

Vehicle	Engine	Tow Limit (lbs)
Acura MDX	3.5 V-6	4,500a,b
Acura RL	3.5 V-6	2,000

a = Requires automatic transmission and power steering coolers when towing more than 2,000 pounds
 b = Maximum rated capacity of 4,500 pounds is for towing boats, 3,500 for towing other trailers.

AM GENERAL

Vehicle	Engine	Tow Limit (lbs)
Hummer 2-dr Hardtop	6.5 V-8 TD	8,300
Hummer 4-dr Open Top	6.5 V-8 TD	8,050
Hummer 4-dr Hardtop	6.5 V-8 TD	7,900
Hummer Station Wagon	6.5 V-8 TD	7,710

TD = Turbodiesel

BMW

Vehicle	Engine	Tow Limit (lbs)
BMW X5	4.4 V-8	6,000a,b
BMW X5	3.0 I-6	6,000a,b,c
BMW X5	3.0 I-6	5,000a,b,d

a = Maximum towing weight for trailers without brakes is 1,650 pounds
 b = Maximum towing weight for trailers with brakes off-road, 3,300 pounds
 c = With manual transmission
 d = With automatic transmission.

BUICK

Vehicle	Engine	Tow Limit (lbs)
Rendezvous	3.4 V-6	3,500a

a = Requires towing package.

CADILLAC

Vehicle	Engine	Tow Limit (lbs)
DeVille	4.6 Northstar V-8	2,000a
Escalade AWD	6000 V-8	8,500
Escalade 2WD	5300 V-8	7,700
Seville SLS	4.6 Northstar V-8	2,000a
Seville STS	4.6 Northstar V-8	3,000a

a = Requires trailer-towing package.

CHEVROLET/GMC

Vehicle	Engine	Tow Limit (lbs)
<i>Astro/Safari Mini-Van</i>		
RWD CV	4300 V-6	5,400a
RWD CV	4300 V-6	5,900b
RWD PV	4300 V-6	5,000a
RWD PV	4300 V-6	5,500b
AWD CV	4300 V-6	5,100a
AWD CV	4300 V-6	5,600b
AWD PV	4300 V-6	4,700a
AWD PV	4300 V-6	5,200b
<i>Avalanche</i>		
1500 CC UUV	5300 V-8	7,300b
1500 CC UUV	5300 V-8	8,300c
1500 CC UUV 4WD	5300 V-8	7,100b
1500 CC UUV 4WD	5300 V-8	8,100c
<i>Express/Savana Van</i>		
G1500 CV	4300 V-6	4,600a
G1500 CV	4300 V-6	5,100b
G1500 CV	5000 V-8	5,600a
G1500 CV	5700 V-8	6,100a
G1500 PV	4300 V-6	4,200a
G1500 PV	4300 V-6	4,700b
G1500 PV	5000 V-8	5,100a
G1500 PV	5700 V-8	5,600a
G1500 PV	5700 V-8	6,600b
G2500 CV	4300 V-6	4,500a
G2500 CV	5000 V-8	5,400a
G2500 CV	5700 V-8	5,900a
G2500 CV HD	4300 V-6	5,200c
G2500 CV HD	5700 V-8	6,600b
G2500 CV HD	5700 V-8	8,100c
G2500 CV HD	6.5 V-8 TD	8,700b/c

G2500 LWB CV	4300 V-6	4,300a
G2500 LWB CV	5000 V-8	5,200a
G2500 LWB CV	5700 V-8	5,700a
G2500 LWB CV HD	4300 V-6	5,000c
G2500 LWB CV HD	5700 V-8	6,400b
G2500 LWB CV HD	5700 V-8	7,900c
G2500 LWB CV HD	6.5 V-8 TD	8,500b/c
G2500 PV	5700 V-8	6,000b
G2500 PV	5700 V-8	7,500c
G2500 PV	6.5 V-8 TD	8,100b/c
G2500 LWB PV	5700 V-8	5,800b
G2500 LWB PV	5700 V-8	7,300c
G3500 CV	5700 V-8	6,400b
G3500 CV	5700 V-8	7,900c
G3500 CV	8100 V-8	7,600a
G3500 CV	8100 V-8	9,100b
G3500 CV	8100 V-8	10,000c
G3500 CV	6.5 V-8 TD	8,600b/c
G3500 LWB CV	5700 V-8	6,300b
G3500 LWB CV	5700 V-8	7,800c
G3500 LWB CV	8100 V-8	7,500a
G3500 LWB CV	8100 V-8	9,000b
G3500 LWB CV	8100 V-8	10,000c
G3500 LWB CV	6.5 V-8 TD	8,400b/c
G3500 PV	5700 V-8	5,900b
G3500 PV	5700 V-8	7,400c
G3500 PV	8100 V-8	7,100a
G3500 PV	8100 V-8	8,600b
G3500 PV	8100 V-8	10,000c
G3500 PV	6.5 V-8 TD	8,000b/c
G3500 LWB PV	5700 V-8	5,600b
G3500 LWB PV	5700 V-8	7,100c
G3500 LWB PV	8100 V-8	6,800a
G3500 LWB PV	8100 V-8	8,300b
G3500 LWB PV	8100 V-8	10,000c
G3500 LWB PV	6.5 V-8 TD	7,800b/c

LWB = Long Wheelbase PV = Passenger Van
 CV = Cargo Van TD = Turbodiesel

a = 3.42:1 axle ratio
 b = 3.73:1 axle ratio
 c = 4.10:1 axle ratio

Blazer/Jimmy

2-dr 2WD	4300 V-6	4,700a,c
2-dr 2WD	4300 V-6	5,700a,d
2-dr 2WD	4300 V-6	4,200b,d
4-dr 2WD	4300 V-6	4,500a,c
4-dr 2WD	4300 V-6	5,500a,d
2-dr 4WD	4300 V-6	4,400a,c
2-dr 4WD	4300 V-6	5,400a,d/e
2-dr 4WD	4300 V-6	3,900b,d
ZR2	4300 V-6	4,800a,e
ZR2	4300 V-6	4,300b,e
4-dr 4WD	4300 V-6	4,200a,c
4-dr 4WD	4300 V-6	5,200a,d/e
4-dr 4WD	4300 V-6	3,700b,d

S-10/Sonoma

Regular cab	2200 I-4	3,200a,f
Regular cab	4300 V-6	4,000a,c
Regular cab	4300 V-6	5,000a,c
Regular cab	4300 V-6	6,000a,d
Extended cab	2200 I-4	2,100b,f
Extended cab	2200 I-4	3,000a,f
Extended cab	4300 V-6	3,800b,c
Extended cab	4300 V-6	4,800a,c
Extended cab	4300 V-6	5,800a,d
Longbed	2200 I-4	2,200b,f
Longbed	2200 I-4	3,100a,f
Longbed	4300 V-6	3,900b,c
Longbed	4300 V-6	4,900a,c
Longbed	4300 V-6	5,900a,d
Regular cab 4WD	4300 V-6	4,200b,d
Regular cab 4WD	4300 V-6	5,700a,d/e
Extended cab 4WD	4300 V-6	4,000b,d
Extended cab 4WD	4300 V-6	5,500a,d/e
ZR2	4300 V-6	4,400b,e
ZR2	4300 V-6	4,900a,e
Crew Cab 4WD	4300 V-6	5,200a,d/e

4WD = Four-wheel drive

a = Automatic transmission

b = Manual transmission

c = 3.08:1 rear axle ratio

d = 3.42:1 rear axle ratio

e = 3.73:1 rear axle ratio

f = 4.10:1 rear axle ratio

Sierra/Silverado, Light-Duty,

Automatic Transmission, Conventional Towing

1500	4300 V-6	4,700a
1500	4300 V-6	5,200c
1500	4800 V-8	6,600c
1500	4800 V-8	7,600d
1500	5300 V-8	7,600c
1500	5300 V-8	8,600d
1500 EC	4300 V-6	4,900c
1500 EC	4300 V-6	5,900d
1500 EC	4800 V-8	6,300c
1500 EC	4800 V-8	7,300d
1500 EC	5300 V-8	7,300c
1500 EC	5300 V-8	8,300d
CC	6000 V-8	8,300d
CC	6000 V-8	10,300e
1500 LB	4300 V-6	4,600a
1500 LB	4300 V-6	5,100c
1500 LB	4800 V-8	6,500c
1500 LB	4800 V-8	7,500d
1500 LB	5300 V-8	7,500c
1500 LB	5300 V-8	8,500d
1500 LB EC	4800 V-8	6,100c
1500 LB EC	4800 V-8	7,100d
1500 LB EC	5300 V-8	7,100c
1500 LB EC	5300 V-8	8,100d
2500 LB	6000 V-8	8,800d
2500 LB	6000 V-8	10,800e
1500 4WD	4300 V-6	4,900c
1500 4WD	4300 V-6	5,400d
1500 4WD	4800 V-8	7,300d
1500 4WD	4800 V-8	8,300e
1500 4WD	5300 V-8	8,300d
1500 4WD	5300 V-8	9,300e
1500 4WD EC	4800 V-8	7,000d
1500 4WD EC	4800 V-8	8,000e
1500 4WD EC	5300 V-8	8,000d
1500 4WD EC	5300 V-8	9,000e
1500 4WD EC	6000 V-8	8,700d
1500 4WD CC	6000 V-8	8,000d
1500 4WD CC	6000 V-8	10,000e
1500 4WD LB	4300 V-6	4,800c
1500 4WD LB	4300 V-6	5,300d
1500 4WD LB	4800 V-8	7,200d
1500 4WD LB	4800 V-8	8,200e
1500 4WD LB	5300 V-8	8,200d
1500 4WD LB	5300 V-8	9,200e
1500 4WD LB EC	4800 V-8	6,800d
1500 4WD LB EC	4800 V-8	7,800e
1500 4WD LB EC	5300 V-8	7,800d
1500 4WD LB EC	5300 V-8	8,800e
2500 4WD EC	6000 V-8	8,300d
2500 4WD EC	6000 V-8	10,300e

Sierra/Silverado, Light-Duty,

Manual Transmission, Conventional Towing

1500	4300 V-6	3,700a
1500	4300 V-6	4,200c
1500	4800 V-8	4,600c
1500	4800 V-8	5,600d
1500 EC	4300 V-6	3,900c
1500 EC	4800 V-8	4,300c
1500 EC	4800 V-8	5,300d
1500 LB	4300 V-6	3,600a
1500 LB	4300 V-6	4,100c
1500 LB	4800 V-8	4,500c
1500 LB	4800 V-8	5,500d
1500 LB EC	4800 V-8	4,100c
1500 LB EC	4800 V-8	5,100d
2500 LB	6000 V-8	8,800d
2500 LB	6000 V-8	10,800e
1500 4WD	4300 V-6	3,900c
1500 4WD	4300 V-6	4,400d
1500 4WD	4800 V-8	5,300d
1500 4WD	4800 V-8	6,300e
1500 4WD EC	4800 V-8	5,000d
1500 4WD EC	4800 V-8	6,000e
1500 4WD LB	4300 V-6	3,800c
1500 4WD LB	4300 V-6	4,300d
1500 4WD LB	4800 V-8	5,200d
1500 4WD LB	4800 V-8	6,200e
1500 4WD LB EC	4800 V-8	4,800d
1500 4WD LB EC	4800 V-8	5,800e
2500 4WD EC	6000 V-8	8,300d
2500 4WD EC	6000 V-8	10,300e

Sierra/Silverado, Light-Duty,

Automatic Transmission, Fifth-Wheel Towing

(Automatic or Manual with 6000 V-8)

1500	4800 V-8	6,600c
1500	4800 V-8	7,600d

1500	5300 V-8	7,600c
1500	5300 V-8	8,600d
1500 EC	4800 V-8	6,300c
1500 EC	4800 V-8	7,300d
1500 EC	5300 V-8	7,300c
1500 EC	5300 V-8	8,300d
1500 CC	6000 V-8	8,300d
1500 CC	6000 V-8	10,300e
1500 LB	4800 V-8	6,500c
1500 LB	4800 V-8	7,500d
1500 LB	5300 V-8	7,500c
1500 LB	5300 V-8	8,500d
1500 LB EC	4800 V-8	6,100c
1500 LB EC	4800 V-8	7,100d
1500 LB EC	5300 V-8	7,100c
1500 LB EC	5300 V-8	8,100d
2500 LB	6000 V-8	8,800d
2500 LB	6000 V-8	10,800e
C3 1500 AWD	6000 V-8	8,700
1500 4WD	4800 V-8	7,300d
1500 4WD	4800 V-8	8,300e
1500 4WD	5300 V-8	8,300d
1500 4WD	5300 V-8	9,300e
1500 4WD EC	4800 V-8	7,000d
1500 4WD EC	4800 V-8	8,000e
1500 4WD EC	5300 V-8	8,000d
1500 4WD EC	5300 V-8	9,000e
1500 4WD CC	6000 V-8	8,700d
1500 4WD CC	6000 V-8	8,000d
1500 4WD CC	6000 V-8	10,000e
1500 4WD LB	4800 V-8	7,200d
1500 4WD LB	4800 V-8	8,200e
1500 4WD LB	5300 V-8	8,200d
1500 4WD LB	5300 V-8	9,200e
1500 4WD LB EC	4800 V-8	6,800d
1500 4WD LB EC	4800 V-8	7,800e
1500 4WD LB EC	5300 V-8	7,800d
1500 4WD LB EC	5300 V-8	8,800e
2500 4WD EC	6000 V-8	8,300d
2500 4WD EC	6000 V-8	10,300e
<i>Sierra/Silverado, Heavy-Duty, Automatic/Manual Transmission, Conventional Towing</i>		
2500 EC	6000 V-8	10,400e
2500 EC	8100 V-8	12,000d/e
2500 EC	6600 V-8 TD	12,000d
2500 CC	6000 V-8	10,200e
2500 CC	8100 V-8	12,000d/e
2500 CC	6600 V-8 TD	12,000d
2500 LB	6000 V-8	10,500e
2500 LB	8100 V-8	12,000d/e
2500 LB	6600 V-8 TD	12,000d
2500 LB EC	6000 V-8	10,200e
2500 LB EC	8100 V-8	12,000d/e
2500 LB EC	6600 V-8 TD	12,000d
2500 LB CC	6000 V-8	10,000e
2500 LB CC	8100 V-8	12,000d/e
2500 LB CC	6600 V-8 TD	12,000d
3500 LB	6000 V-8	10,100e
3500 LB	8100 V-8	12,000e
3500 LB	6600 V-8 TD	12,000d
3500 LB EC	6000 V-8	9,800e
3500 LB EC	8100 V-8	12,000e
3500 LB EC	6600 V-8 TD	12,000d
3500 LB CC	6000 V-8	9,500e
3500 LB CC	8100 V-8	12,000e
3500 LB CC	6600 V-8 TD	12,000d
3500 LB CC	6600 V-8 TD	12,000d
2500 4WD EC	6000 V-8	10,200e
2500 4WD EC	8100 V-8	12,000d/e
2500 4WD EC	6600 V-8 TD	12,000d
2500 4WD CC	6000 V-8	9,900e
2500 4WD CC	8100 V-8	12,000d/e
2500 4WD CC	6600 V-8 TD	12,000d
2500 4WD LB	6000 V-8	10,300e
2500 4WD LB	8100 V-8	12,000d/e
2500 4WD LB	6600 V-8 TD	12,000d
2500 4WD LB EC	6000 V-8	9,900e
2500 4WD LB EC	8100 V-8	12,000d/e
2500 4WD LB EC	6600 V-8 TD	12,000d
2500 4WD LB CC	6000 V-8	9,700e
2500 4WD LB CC	8100 V-8	12,000d/e
2500 4WD LB CC	6600 V-8 TD	12,000d
3500 4WD LB	6000 V-8	9,800e
3500 4WD LB	8100 V-8	12,000e
3500 4WD LB	6600 V-8 TD	12,000d
3500 4WD LB EC	6000 V-8	9,400e
3500 4WD LB EC	8100 V-8	12,000e

3500 4WD LB EC	6600 V-8 TD	12,000d
3500 4WD LB CC	6000 V-8	9,200e
3500 4WD LB CC	8100 V-8	12,000e
3500 4WD LB CC	6600 V-8 TD	12,000d
<i>Sierra/Silverado, Heavy-Duty, Automatic/Manual Transmission, Fifth-Wheel Towing</i>		
2500 EC	6000 V-8	10,400e
2500 EC	8100 V-8	13,800d
2500 EC	8100 V-8	15,800e
2500 EC	6600 V-8 TD	15,700d
2500 CC	6000 V-8	10,200e
2500 CC	8100 V-8	13,500d
2500 CC	8100 V-8	15,500e
2500 CC	6600 V-8 TD	15,400d
2500 LB	6000 V-8	10,500e
2500 LB	8100 V-8	13,900d
2500 LB	8100 V-8	15,900e
2500 LB	6600 V-8 TD	15,800d
2500 LB EC	6000 V-8	10,200e
2500 LB EC	8100 V-8	13,600d
2500 LB EC	8100 V-8	15,600e
2500 LB EC	6600 V-8 TD	15,400d
2500 LB CC	6000 V-8	10,000e
2500 LB CC	8100 V-8	13,400d
2500 LB CC	8100 V-8	15,400e
2500 LB CC	6600 V-8 TD	15,200d
3500 LB	6000 V-8	10,100e
3500 LB	8100 V-8	15,700e
3500 LB	6600 V-8 TD	15,600d
3500 LB EC	6000 V-8	9,800e
3500 LB EC	8100 V-8	15,400e
3500 LB EC	6600 V-8 TD	15,200d
3500 LB CC	6000 V-8	9,500e
3500 LB CC	8100 V-8	15,200e
3500 LB CC	6600 V-8 TD	15,000d
2500 4WD EC	6000 V-8	10,200e
2500 4WD EC	8100 V-8	13,500d
2500 4WD EC	8100 V-8	15,500e
2500 4WD EC	6600 V-8 TD	15,300d
2500 4WD CC	6000 V-8	9,900e
2500 4WD CC	8100 V-8	13,100d
2500 4WD CC	8100 V-8	15,100e
2500 4WD CC	6600 V-8 TD	15,100d
2500 4WD LB	6000 V-8	10,300e
2500 4WD LB	8100 V-8	13,700d
2500 4WD LB	8100 V-8	15,700e
2500 4WD LB	6600 V-8 TD	15,500d
2500 4WD LB EC	6000 V-8	9,900e
2500 4WD LB EC	8100 V-8	13,300d
2500 4WD LB EC	8100 V-8	15,300e
2500 4WD LB EC	6600 V-8 TD	15,100d
2500 4WD LB CC	6000 V-8	9,700e
2500 4WD LB CC	8100 V-8	13,100d
2500 4WD LB CC	8100 V-8	15,100e
2500 4WD LB CC	6600 V-8 TD	14,900d
3500 4WD LB	6000 V-8	9,800e
3500 4WD LB	8100 V-8	15,500e
3500 4WD LB	6600 V-8 TD	15,300d
3500 4WD LB EC	6000 V-8	9,400e
3500 4WD LB EC	8100 V-8	15,100e
3500 4WD LB EC	6600 V-8 TD	14,900d
3500 4WD LB CC	6000 V-8	9,200e
3500 4WD LB CC	8100 V-8	14,900e
3500 4WD LB CC	6600 V-8 TD	14,700d
<i>Tahoe/Yukon</i>		
1500	4800 V-8	5,900c
1500	4800 V-8	6,900d
1500	5300 V-8	6,900c
1500	5300 V-8	7,900d
Suburban/Yukon XL 1500	5300 V-8	7,800d
Suburban/Yukon XL 1500	5300 V-8	8,800e
1500 4WD	4800 V-8	6,700d
1500 4WD	4800 V-8	7,700e
1500 4WD	5300 V-8	7,700d
1500 4WD	5300 V-8	8,700e
Denali 1500 AWD	6000 V-8	8,500d
Suburban/Yukon XL 1500 4WD	5300 V-8	7,600d
Suburban/Yukon XL 1500 4WD	5300 V-8	8,600e
Yukon XL Denali 1500 AWD	6000 V-8	8,400d
Suburban/Yukon XL 2500	6000 V-8	8,300d
Suburban/Yukon XL 2500	6000 V-8	10,300e
Suburban/Yukon XL 2500	8100 V-8	10,900d
Suburban/Yukon XL 2500	8100 V-8	12,000e
Suburban/Yukon XL 2500 4WD	6000 V-8	8,000d
Suburban/Yukon XL 2500 4WD	6000 V-8	10,000e
Suburban/Yukon XL 2500 4WD	8100 V-8	10,500d

Suburban/Yukon XL 2500 4WD	8100 V-8	12,000e
Venture	3400 V-6	3,500g

LD = Light-Duty HD = Heavy-Duty TD = Turbodiesel
 EC = Extended Cab CC = Crew Cab LB = Long Bed
 4WD = Four-Wheel Drive

Note: Weight-distributing hitch and sway control required over 5,000 pounds trailer weight on light-duty models, 7,500 pounds on heavy-duty models.

- a = Requires 3.08:1 axle ratio
- b = Requires 3.23:1 axle ratio
- c = Requires 3.42:1 axle ratio
- d = Requires 3.73:1 axle ratio
- e = Requires 4.10:1 axle ratio
- f = Requires automatic transmission
- g = Requires heavy-duty tow package

DAIMLERCHRYSLER

CHRYSLER

Vehicle	Engine	Tow Limit (lbs)
Concorde	3.2 V-6	2,000a
300M, LHS	3.5 V-6	2,000a
Town & Country Van	3.3, 3.8 V-6	3,500a,b

- a = Requires towing package
- b = Requires a Class II load-equalizing hitch.

DODGE

Vehicle	Engine	Tow Limit (lbs)
Caravan	3.3, 3.8 V-6	3500i
Dakota	2.5 I-4	2,250a,g
Dakota	3.9 V-6	3,750a,e
Dakota	3.9 V-6	4,250a,f
Dakota	3.9 V-6	5,050d,f
Dakota	3.9 V-6	5,450d,g
Dakota	4.7 V-8	5,700a,f
Dakota	4.7 V-8	6,700a,g
Dakota	4.7 V-8	5,350d,f
Dakota	4.7 V-8	6,650d,g
Dakota R/T	5.9 V-8	2,000d,g
Dakota 4WD	3.9 V-6	4,000a,f
Dakota 4WD	3.9 V-6	4,800a,g
Dakota 4WD	3.9 V-6	5,200d,g
Dakota 4WD	4.7 V-8	5,400a,f
Dakota 4WD	4.7 V-8	6,400a,g
Dakota 4WD	4.7 V-8	5,050d,f
Dakota 4WD	4.7 V-8	6,350d,g
Dakota Club Cab	2.5 I-4	2,050a,g
Dakota Club Cab	3.9 V-6	3,550a,e
Dakota Club Cab	3.9 V-6	4,050a,f
Dakota Club Cab	3.9 V-6	4,850a,g
Dakota Club Cab	3.9 V-6	4,800d,f
Dakota Club Cab	3.9 V-6	5,200d,g
Dakota Club Cab	4.7 V-8	5,450a,f
Dakota Club Cab	4.7 V-8	6,450a,g
Dakota Club Cab	4.7 V-8	5,150d,f
Dakota Club Cab	4.7 V-8	6,450d,g
Dakota R/T Club Cab	5.9 V-8	2,000d,g
Dakota Club Cab 4WD	3.9 V-6	3,800a,f
Dakota Club Cab 4WD	3.9 V-6	4,600a,g
Dakota Club Cab 4WD	3.9 V-6	5,000d,g
Dakota Club Cab 4WD	4.7 V-8	5,200a,f
Dakota Club Cab 4WD	4.7 V-8	6,200a,g
Dakota Club Cab 4WD	4.7 V-8	4,850d,f
Dakota Club Cab 4WD	4.7 V-8	6,150d,g
Dakota Quad Cab	3.9 V-6	3,200a,e
Dakota Quad Cab	3.9 V-6	3,700a,f
Dakota Quad Cab	3.9 V-6	4,500a,g
Dakota Quad Cab	3.9 V-6	4,500d,f
Dakota Quad Cab	3.9 V-6	4,900d,g
Dakota Quad Cab	4.7 V-8	5,150a,f
Dakota Quad Cab	4.7 V-8	6,150a,g
Dakota Quad Cab	4.7 V-8	4,800d,f
Dakota Quad Cab	4.7 V-8	6,100d,g
Dakota Quad Cab	5.9 V-8	4,650d,f
Dakota Quad Cab	5.9 V-8	6,250d,g
Dakota Quad Cab 4WD	3.9 V-6	3,400a,f
Dakota Quad Cab 4WD	3.9 V-6	4,200a,g
Dakota Quad Cab 4WD	3.9 V-6	4,600d,g
Dakota Quad Cab 4WD	4.7 V-8	4,900a,f
Dakota Quad Cab 4WD	4.7 V-8	5,900a,g
Dakota Quad Cab 4WD	4.7 V-8	4,850d,f
Dakota Quad Cab 4WD	4.7 V-8	5,850d,g
Dakota Quad Cab 4WD	5.9 V-8	4,500d,f
Dakota Quad Cab 4WD	5.9 V-8	6,100d,g
Durango	4.7 V-8	4,750f

Durango	4.7 V-8	6,050g
Durango	5.9 V-8	5,950f
Durango	5.9 V-8	7,650g
Durango 4WD	4.7 V-8	4,450f
Durango 4WD	4.7 V-8	5,750g
Durango 4WD	5.9 V-8	5,650f
Durango 4WD	5.9 V-8	7,350g
Intrepid	All	2,000
<i>Ram Van 1500</i>		
109* Wheelbase	3.9 V-6	4,450c,f
109* Wheelbase	5.2 V-8	5,450d,f
109* Wheelbase	5.2 V-8	5,950d,g
127* Wheelbase	3.9 V-6	4,250c,f
127* Wheelbase	5.2 V-8	6,750d,f
127* Wheelbase	5.2 V-8	7,750d,g
127* Wheelbase	5.9 V-8	7,200d,f
127* Wheelbase	5.9 V-8	8,200d,g
127* Wheelbase Maxi	3.9 V-6	4,150c,f
127* Wheelbase Maxi	5.2 V-8	6,650d,f
127* Wheelbase Maxi	5.9 V-8	7,150d,f
127* Wheelbase Maxi	5.9 V-8	8,150d,g
<i>Ram Van 2500</i>		
127* Wheelbase	3.9 V-6	4,050c,g
127* Wheelbase	5.2 V-8	7,600d,f
127* Wheelbase	5.2 V-8	8,100d,g
127* Wheelbase	5.9 V-8	8,100d,g
127* Wheelbase	5.9 V-8	8,600d,h
127* Wheelbase Maxi	5.2 V-8	7,450d,h
127* Wheelbase Maxi	5.2 V-8	7,950d,h
127* Wheelbase Maxi	5.9 V-8	7,900d,g
127* Wheelbase Maxi	5.9 V-8	8,400d,h
<i>Ram Van 3500</i>		
127* Wheelbase	5.2 V-8	7,550d,g
127* Wheelbase	5.2 V-8	8,050d,h
127* Wheelbase	5.9 V-8	8,100d,g
127* Wheelbase	5.9 V-8	8,600d,h
127* Wheelbase Maxi	5.2 V-8	7,400d,g
127* Wheelbase Maxi	5.2 V-8	7,900d,h
127* Wheelbase Maxi	5.9 V-8	7,850d,g
127* Wheelbase Maxi	5.9 V-8	8,350d,h
<i>Ram Wagon 1500</i>		
109* Wheelbase	3.9 V-6	4,050c,f
109* Wheelbase	5.2 V-8	5,050d,f
109* Wheelbase	5.2 V-8	5,550d,g
<i>Ram Wagon 2500</i>		
127* Wheelbase	5.2 V-8	7,200d,g
127* Wheelbase	5.2 V-8	7,700d,h
127* Wheelbase	5.9 V-8	7,650d,f
127* Wheelbase	5.9 V-8	8,150d,g
<i>Ram Wagon 3500</i>		
127* Wheelbase Maxi	5.2 V-8	6,750d,g
127* Wheelbase Maxi	5.2 V-8	7,250d,h
127* Wheelbase Maxi	5.9 V-8	7,200d,f
127* Wheelbase Maxi	5.9 V-8	7,700d,g
<i>Ram Trucks</i>		
1500	3.9 V-6	3,500a,f*
1500	3.9 V-6	3,350a,f
1500	3.9 V-6	3,300d,f*
1500	3.9 V-6	3,150d,f
1500	5.2 V-8	3,250a,e
1500	5.2 V-8	4,950a,f
1500	5.2 V-8	7,950d,f/g
1500	5.9 V-8	7,900d,f/g
<i>*Work Special.</i>		
1500 4WD	5.2 V-8	4,650a,f
1500 4WD	5.2 V-8	5,150a,g/h*
1500 4WD	5.2 V-8	7,550d,f/g/h*
1500 4WD	5.9 V-8	7,550d,f/g/h*
<i>*Off-road Group.</i>		
1500 Club Cab	5.2 V-8	4,600a,f
1500 Club Cab	5.2 V-8	7,600d,f/g
1500 Club Cab	5.9 V-8	7,550d,f/g
1500 Club Cab 4WD	5.2 V-8	4,300a,f
1500 Club Cab 4WD	5.2 V-8	4,800a,g
1500 Club Cab 4WD	5.2 V-8	7,250d,f/g
1500 Club Cab 4WD	5.9 V-8	7,200d,f/g/h*
<i>*Off-road Group.</i>		
1500 Quad Cab	5.2 V-8	4,500a,f
1500 Quad Cab	5.2 V-8	7,500d,f/g
1500 Quad Cab	5.9 V-8	7,500d,f/g
1500 Quad Cab 4WD	5.2 V-8	4,200a,f
1500 Quad Cab 4WD	5.2 V-8	4,700a,g
1500 Quad Cab 4WD	5.2 V-8	7,150d,f/g
1500 Quad Cab 4WD	5.9 V-8	7,150d,f/g/h*
<i>*Off-road Group.</i>		
2500	5.9 V-8	8,800a,f/h
2500	5.9 V-8	8,850d,f/h

2500	5.9 I-6 TD	13,950b,f/h
2500	5.9 I-6 TD	14,100a,f/h
2500	5.9 I-6 TD	10,150d,f
2500	5.9 I-6 TD	12,150d,h
2500	8.0 V-10	13,350a,f/h
2500	8.0 V-10	13,450d,f/h
2500 4WD	5.9 V-8	8,350a,f/h
2500 4WD	5.9 V-8	8,400d,f/h
2500 4WD	5.9 I-6 TD	13,450b,f/h
2500 4WD	5.9 I-6 TD	13,650a,f/h
2500 4WD	5.9 I-6 TD	9,700d,f
2500 4WD	5.9 I-6 TD	11,700d,f/h
2500 4WD	8.0 V-10	12,950a/d,f/h
2500 Quad Cab	5.9 V-8	8,500a,f/h
2500 Quad Cab	5.9 V-8	8,550d,f/h
2500 Quad Cab	5.9 I-6 TD	13,650b,f/h
2500 Quad Cab	5.9 I-6 TD	13,800a,f/h
2500 Quad Cab	5.9 I-6 TD	9,850d,f
2500 Quad Cab	5.9 I-6 TD	11,850d,h
2500 Quad Cab	8.0 V-10	13,050a,f/h
2500 Quad Cab	8.0 V-10	13,150d,f/h
2500 Quad Cab 4WD	5.9 V-8	8,050a,f/h
2500 Quad Cab 4WD	5.9 V-8	8,100d,f/h
2500 Quad Cab 4WD	5.9 I-6 TD	13,200b,f/h
2500 Quad Cab 4WD	5.9 I-6 TD	13,400a,f/h
2500 Quad Cab 4WD	5.9 I-6 TD	9,450d,f
2500 Quad Cab 4WD	5.9 I-6 TD	11,450d,h
2500 Quad Cab 4WD	8.0 V-10	12,650a,f/h
2500 Quad Cab 4WD	8.0 V-10	12,700d,f/h
3500	5.9 V-8	9,400a,f/h
3500	5.9 V-8	9,450d,f/h
3500	5.9 I-6 TD	13,650b,f
3500	5.9 I-6 TD	15,150b,h
3500	5.9 I-6 TD	13,800a,f/h
3500	5.9 I-6 TD	9,850d,f
3500	5.9 I-6 TD	12,850d,h
3500	8.0 V-10	13,050a,f/h
3500	8.0 V-10	13,100d,f/h
3500 4WD	5.9 V-8	9,000d,f/h
3500 4WD	5.9 I-6 TD	13,200b,f
3500 4WD	5.9 I-6 TD	14,700b,h
3500 4WD	5.9 I-6 TD	13,350a,f/h
3500 4WD	5.9 I-6 TD	9,400d,f
3500 4WD	5.9 I-6 TD	12,400d,h
3500 4WD	8.0 V-10	12,600a,f/h
3500 4WD	8.0 V-10	12,650d,f/h
3500 Quad Cab	5.9 V-8	8,950a,f/h
3500 Quad Cab	5.9 V-8	9,000d,f/h
3500 Quad Cab	5.9 I-6 TD	13,200b,f
3500 Quad Cab	5.9 I-6 TD	14,700b,h
3500 Quad Cab	5.9 I-6 TD	13,400a,f/h
3500 Quad Cab	5.9 I-6 TD	9,450d,f
3500 Quad Cab	5.9 I-6 TD	12,450d,h
3500 Quad Cab	8.0 V-10	12,650a,f/h
3500 Quad Cab	8.0 V-10	12,700d,f/h
3500 Quad Cab 4WD	5.9 V-8	8,550a,f/h
3500 Quad Cab 4WD	5.9 V-8	8,600d,f/h
3500 Quad Cab 4WD	5.9 I-6 TD	12,800b,f
3500 Quad Cab 4WD	5.9 I-6 TD	14,300b,h
3500 Quad Cab 4WD	5.9 I-6 TD	12,950a,f/h
3500 Quad Cab 4WD	5.9 I-6 TD	9,000d,f
3500 Quad Cab 4WD	5.9 I-6 TD	12,000d,h
3500 Quad Cab 4WD	8.0 V-10	12,200a,f/h
3500 Quad Cab 4WD	8.0 V-10	12,250d,f/h
<i>*Not available in California</i>		
<i>Note: Tow ratings over 10,000 pounds are for fifth-wheels (except vans).</i>		
TD= Turbodiesel		
a = five-speed manual		
b = six-speed manual		
c = three-speed automatic		
d = four-speed automatic		
e = 3.21 axle; f = 3.55 axle		
g = 3.92 axle		
h = 4.10 axle		
i = optional towing package.		
FORD		
Vehicle	Engine	Tow Limit (lbs)
Crown Victoria	4.6 V-8	2,000
Econoline		
Van E-150	4.2 V-6	5,100c
Van E-150	4.6 V-8	6,600c
Van E-150	5.4 V-8	7,000c
Wagon E-150	4.2 V-6	4,700c

Wagon E-150	4.6 V-8	6,200c
Wagon E-150	5.4 V-8	6,600c
Van E-250	4.2 V-6	5,300d
Van E-250	4.2 V-6	5,700e
Van E-250	5.4 V-8	7,500d
Van E-250 NGV	5.4 V-8	7,500d
Van E-250 Ext	4.2 V-6	5,100d
Van E-250 Ext	4.2 V-6	5,500e
Van E-250 Ext	5.4 V-8	7,200d
Van E-250 NGV Ext	5.4 V-8	7,300d
Van E-350	5.4 V-8	6,500c
Van E-350	5.4 V-8	7,500e
Van E-350 NGV	5.4 V-8	6,900e
Van E-350	6.8 V-10	9,600d
Van E-350	6.8 V-10	10,000e
Van E-350	7.3 V-8 TD	9,900c
Van E-350	7.3 V-8 TD	10,000e
Van E-350 Ext	5.4 V-8	6,300c
Van E-350 Ext	5.4 V-8	7,300e
Van E-350 NGV Ext	5.4 V-8	6,800e
Van E-350 Ext	6.8 V-10	9,200d
Van E-350 Ext	6.8 V-10	10,000e
Van E-350 Ext	7.3 V-8 TD	9,700c
Van E-350 Ext	7.3 V-8 TD	10,000e
Wagon E-350	5.4 V-8	6,000c
Wagon E-350	5.4 V-8	7,000e
Wagon E-350 NGV	5.4 V-8	6,500e
Wagon E-350	6.8 V-10	8,900d
Wagon E-350	6.8 V-10	10,000e
Wagon E-350	7.3 V-8 TD	9,500c
Wagon E-350	7.3 TD	10,000e
Wagon E-350 Ext	5.4 V-8	5,700c
Wagon E-350 Ext	5.4 V-8	6,700e
Wagon E-350 NGV Ext	5.4 V-8	6,200e
Wagon E-350 Ext	6.8 V-10	8,600d
Wagon E-350 Ext	6.8 V-10	10,000e
Wagon E-350 Ext	7.3 V-8 TD	9,100c
Wagon E-350 Ext	7.3 V-8 TD	10,000e
Escape	3.0 V-6	3,500n
<i>Excursion</i>		
2WD	5.4 V-8	6,200d
2WD	6.8 V-10	12,500d/j
All	7.3 V-8 TD	12,500d
4WD	5.4 V-8	7,200e
4WD	6.8 V-10	9,600d
4WD	6.8 V-10	12,500j
<i>Expedition</i>		
2WD	4.6 V-8	5,800b
2WD	5.4 V-8	6,600b
2WD	5.4 V-8	7,600c,g
2WD	5.4 V-8	8,100d,g
4WD	4.6 V-8	5,500c,h
4WD	4.6 V-8	6,000c,g
4WD	5.4 V-8	6,300b
4WD	5.4 V-8	7,300c,f
4WD	5.4 V-8	6,800c,h
4WD	5.4 V-8	7,800d,g,m
4WD	5.4 V-8	7,300d,h,m
<i>Explorer Sport (2-dr) and Sport Trac, Manual Transmission</i>		
Sport	4.0 V-6	3,080
Sport 4WD	4.0 V-6	2,880
Sport Trac	4.0 V-6	2,740
Sport Trac 4WD	4.0 V-6	2,520
<i>Explorer Sport (2-dr) and Sport Trac, Automatic Transmission</i>		
Sport	4.0 V-6	5,140
Sport 4WD	4.0 V-6	4,940
Sport Trac	4.0 V-6	5,300
Sport Trac 4WD	4.0 V-6	5,080
<i>Explorer (4-Dr), 5-spd Automatic Only</i>		
2WD	4.0 V-6	4,940c
2WD	4.0 V-6	5,940d/e
2WD	5.0 V-8	5,820c
2WD	5.0 V-8	6,820d
4WD	4.0 V-6	4,740c
4WD	4.0 V-6	5,740d/e
4WD	5.0 V-8	5,620c
4WD	5.0 V-8	6,620d
<i>F-150, Manual Transmission, Conventional Towing</i>		
Reg cab	4.2 V-6	2,000a
Reg cab	4.2 V-6	3,600c
Reg cab	4.6 V-8	2,000a
Reg cab	4.6 V-8	2,900b
Reg cab	4.6 V-8	3,400c
Reg cab 4WD	4.2 V-6	2,600b
Reg cab 4WD	4.2 V-6	3,200c

Reg cab 4WD	4.6 V-8	2,500b
Reg cab 4WD	4.6 V-8	3,100c
SuperCab	4.2 V-6	2,000a
SuperCab	4.2 V-6	3,300c
SuperCab	4.6 V-8	2,000a
SuperCab	4.6 V-8	2,600b
SuperCab	4.6 V-8	3,200c
SuperCab 4WD	4.6 V-8	2,300b
SuperCab 4WD	4.6 V-8	2,900c

*F-150, Automatic Transmission,
Conventional Towing*

Reg cab	4.2 V-6	4,800b
Reg cab	4.2 V-6	5,800c
Reg cab	4.6 V-8	2,000a
Reg cab	4.6 V-8	6,200b
Reg cab	4.6 V-8	7,200c,g
Reg cab	5.4 V-8	7,600b
Reg cab	5.4 V-8	8,600c,g
Reg cab	5.4 V-8	8,800d
Reg cab NGV	5.4 V-8	5,900d
Reg cab 4WD	4.2 V-6	5,400c
Reg cab 4WD	4.6 V-8	5,800b
Reg cab 4WD	4.6 V-8	6,800c,g
Reg cab 4WD	4.6 V-8	6,300c,h
Reg cab 4WD	5.4 V-8	7,200b
Reg cab 4WD	5.4 V-8	8,200c,g
Reg cab 4WD	5.4 V-8	7,700c,h
Reg cab 4WD	5.4 V-8	8,400d
SuperCab	4.2 V-6	5,500c
Super Cab	4.6 V-8	2,000a
Super Cab	4.6 V-8	5,900b
Super Cab	4.6 V-8	6,900c,g
SuperCab	5.4 V-8	7,300b
SuperCab	5.4 V-8	8,400c,g
SuperCab	5.4 V-8	8,600d
SuperCab 4WD	4.6 V-8	5,600b
SuperCab 4WD	4.6 V-8	6,600c,g
SuperCab 4WD	4.6 V-8	6,100c,h
SuperCab 4WD	5.4 V-8	7,000b
SuperCab 4WD	5.4 V-8	8,000c,g
SuperCab 4WD	5.4 V-8	7,500c,h
SuperCab 4WD	5.4 V-8	8,300d
SuperCrew	4.6 V-8	6,600c,g
SuperCrew	5.4 V-8	8,000c,g
SuperCrew 4WD	4.6 V-8	5,700c,h
SuperCrew 4WD	4.6 V-8	6,200c,g
SuperCrew 4WD	5.4 V-8	7,700c,g
SuperCrew 4WD	5.4 V-8	7,200c,h

*F-150, Automatic Transmission,
Fifth-Wheel Towing*

Reg cab	4.2 V-6	5,800c
Reg cab	4.6 V-8	7,200c,g
Reg cab	5.4 V-8	8,700c,g
Reg cab	5.4 V-8	8,800d
Reg cab 4WD	4.2 V-6	5,400c
Reg cab4WD	4.6 V-8	6,300c,h
Reg cab 4WD	4.6 V-8	6,800c,g
Reg cab4WD	5.4 V-8	8,300c,g
Reg cab 4WD	5.4 V-8	7,800c,h
Reg cab4WD	5.4 V-8	8,400d
SuperCab	4.2 V-6	5,500c
SuperCab	4.6 V-8	7,000c,g
SuperCab	5.4 V-8	8,400c,g
SuperCab	5.4 V-8	8,600d
SuperCab 4WD	4.6 V-8	6,600c,g
SuperCab 4WD	4.6 V-8	6,100c,h
SuperCab 4WD	5.4 V-8	8,000c,g
SuperCab 4WD	5.4 V-8	7,500c,h
SuperCab 4WD	5.4 V-8	8,300d

Super Duty F-250/F-350,

Manual Transmission, Conventional Towing

F-250	5.4 V-8	8,200d
F-250	5.4 V-8	9,700e
F-250	6.8 V-10	12,500d/j
F-250	7.3 V-8 TD	12,500d
F-250 4WD	5.4 V-8	7,700d
F-250 4WD	5.4 V-8	9,200e
F-250 4WD	6.8 V-10	12,500d/j
F-250 4WD	7.3 V-8 TD	12,500d
F-250 SuperCab	5.4 V-8	7,800d
F-250 SuperCab	5.4 V-8	9,300e
F-250 SuperCab	6.8 V-10	12,500d/j
F-250 SuperCab	7.3 V-8 TD	12,500d
F-250 SuperCab 4WD	5.4 V-8	7,400d
F-250 SuperCab 4WD	5.4 V-8	8,900e
F-250 SuperCab 4WD	6.8 V-10	12,500d/j
F-250 SuperCab 4WD	7.3 V-8 TD	12,500d

F-250 Crew Cab	5.4 V-8	7,500d
F-250 Crew Cab	5.4 V-8	9,000e
F-250 Crew Cab	6.8 V-10	12,500d/j
F-250 Crew Cab	7.3 V-8 TD	12,500d
F-250 Crew Cab 4WD	5.4 V-8	7,100d
F-250 Crew Cab 4WD	5.4 V-8	8,600e
F-250 Crew Cab 4WD	6.8 V-10	12,500d/j
F-250 Crew Cab 4WD	7.3 V-8 TD	12,500d
F-350	5.4 V-8	8,100d
F-350	5.4 V-8	9,600e
F-350	6.8 V-10	12,500d/j
F-350	7.3 V-8 TD	12,500d
F-350 DRW	5.4 V-8	7,800d
F-350 DRW	5.4 V-8	9,300e
F-350 DRW	6.8 V-10	12,500d/j
F-350 DRW	7.3 V-8 TD	12,500d/e
F-350 4WD	5.4 V-8	7,700d
F-350 4WD	5.4 V-8	9,200e
F-350 4WD	6.8 V-10	12,500d/j
F-350 4WD	7.3 V-8 TD	12,500d
F-350 4WD DRW	5.4 V-8	7,400d
F-350 4WD DRW	5.4 V-8	8,900e
F-350 4WD DRW	6.8 V-10	12,500d/j
F-350 4WD DRW	7.3 V-8 TD	12,500d/e
F-350 SuperCab	5.4 V-8	7,800d
F-350 SuperCab	5.4 V-8	9,300e
F-350 SuperCab	6.8 V-10	12,500d/j
F-350 SuperCab	7.3 V-8 TD	12,500d
F-350 SuperCab DRW	5.4 V-8	7,500d
F-350 SuperCab DRW	5.4 V-8	9,000e
F-350 SuperCab DRW	6.8 V-10	12,500d/j
F-350 SuperCab DRW	7.3 V-8 TD	12,500d/e
F-350 SuperCab 4WD	5.4 V-8	7,400d
F-350 SuperCab 4WD	5.4 V-8	8,900e
F-350 SuperCab 4WD	6.8 V-10	12,500d/j
F-350 SuperCab 4WD	7.3 V-8 TD	12,500d
F-350 SuperCab 4WD DRW	5.4 V-8	7,200d
F-350 SuperCab 4WD DRW	5.4 V-8	8,700e
F-350 SuperCab 4WD DRW	6.8 V-10	12,500d/j
F-350 SuperCab 4WD DRW	7.3 V-8 TD	12,500d/e
F-350 Crew Cab	5.4 V-8	7,500d
F-350 Crew Cab	5.4 V-8	9,000e
F-350 Crew Cab	6.8 V-10	12,500d/j
F-350 Crew Cab	7.3 V-8 TD	12,500d
F-350 Crew Cab DRW	6.8 V-10	12,500d/j
F-350 Crew Cab RW	7.3 V-8 TD	12,500d/e
F-350 Crew Cab 4WD	5.4 V-8	7,100d
F-350 Crew Cab 4WD	5.4 V-8	8,600e
F-350 Crew Cab 4WD	6.8 V-10	12,500d/j
F-350 Crew Cab 4WD	7.3 V-8 TD	12,500d
F-350 Crew Cab 4WD DRW	6.8 V-10	9,600d
F-350 Crew Cab 4WD DRW	6.8 V-10	12,500j
F-350 Crew Cab 4WD DRW	7.3 V-8 TD	12,500d/e

Super Duty F-250/F-350,

Automatic Transmission, Conventional Towing

F-250	5.4 V-8	8,100d
F-250	5.4 V-8	9,600e
F-250 all models	6.8 V-10	12,500
F-250 all models	7.3 V-8 TD	12,500
F-250 4WD	5.4 V-8	7,600d
F-250 4WD	5.4 V-8	9,100e
F-250 SuperCab	5.4 V-8	7,700d
F-250 SuperCab	5.4 V-8	9,200e
F-250 SuperCab 4WD	5.4 V-8	7,300d
F-250 SuperCab 4WD	5.4 V-8	8,800e
F-250 Crew Cab	5.4 V-8	7,400d
F-250 Crew Cab	5.4 V-8	8,900e
F-250 Crew Cab 4WD	5.4 V-8	7,100d
F-250 Crew Cab 4WD	5.4 V-8	8,600e
F-350	5.4 V-8	8,000d
F-350	5.4 V-8	9,500e
F-350 all models	6.8 V-10	12,500
F-350 all models	7.3 V-8 TD	12,500
F-350 DRW	5.4 V-8	7,800d
F-350 DRW	5.4 V-8	9,300e
F-350 4WD	5.4 V-8	7,600d
F-350 4WD	5.4 V-8	9,100e
F-350 4WD DRW	5.4 V-8	7,300d
F-350 4WD DRW	5.4 V-8	8,800e
F-350 SuperCab	5.4 V-8	7,700d
F-350 SuperCab	5.4 V-8	9,200e
F-350 SuperCab DRW	5.4 V-8	7,500d
F-350 SuperCab DRW	5.4 V-8	9,000e
F-350 SuperCab 4WD	5.4 V-8	7,300d
F-350 SuperCab 4WD	5.4 V-8	8,800e
F-350 SuperCab 4WD DRW	5.4 V-8	7,100d
F-350 SuperCab 4WD DRW	5.4 V-8	8,600e

F-350 Crew Cab	5.4 V-8	7,400d
F-350 Crew Cab	5.4 V-8	8,900e
F-350 Crew Cab 4WD	5.4 V-8	7,100d
F-350 Crew Cab 4WD	5.4 V-8	8,600e
<i>Super Duty F-250/F-350, Manual Transmission, Fifth-Wheel Towing</i>		
F-250	5.4 V-8	8,200d
F-250	5.4 V-8	9,700e
F-250	6.8 V-10	11,000d
F-250	6.8 V-10	14,500j
F-250	7.3 V-8 TD	14,000d
F-250 4WD	5.4 V-8	7,700d
F-250 4WD	5.4 V-8	9,200e
F-250 4WD	6.8 V-10	10,500d
F-250 4WD	6.8 V-10	14,000j
F-250 4WD	7.3 V-8 TD	13,500d
F-250 SuperCab	5.4 V-8	7,800d
F-250 SuperCab	5.4 V-8	9,300e
F-250 SuperCab	6.8 V-10	10,600d
F-250 SuperCab	6.8 V-10	14,100j
F-250 SuperCab	7.3 V-8 TD	13,600d
F-250 SuperCab 4WD	5.4 V-8	7,400d
F-250 SuperCab 4WD	5.4 V-8	8,900e
F-250 SuperCab 4WD	6.8 V-10	10,200d
F-250 SuperCab 4WD	6.8 V-10	13,700j
F-250 SuperCab 4WD	7.3 V-8 TD	13,200d
F-250 Crew Cab	5.4 V-8	7,500d
F-250 Crew Cab	5.4 V-8	9,000e
F-250 Crew Cab	6.8 V-10	10,300d
F-250 Crew Cab	7.3 V-8 TD	13,300d
F-250 Crew Cab 4WD	5.4 V-8	7,100d
F-250 Crew Cab 4WD	5.4 V-8	8,600e
F-250 Crew Cab 4WD	6.8 V-10	10,000d
F-250 Crew Cab 4WD	6.8 V-10	13,500j
F-250 Crew Cab 4WD	7.3 V-8 TD	12,900d
F-350	5.4 V-8	8,100d
F-350	5.4 V-8	9,600e
F-350	6.8 V-10	10,900d
F-350	6.8 V-10	14,400j
F-350	7.3 V-8 TD	13,900d
F-350 DRW	5.4 V-8	7,800d
F-350 DRW	5.4 V-8	9,300e
F-350 DRW	6.8 V-10	10,600d
F-350 DRW	6.8 V-10	14,100j
F-350 DRW	7.3 V-8 TD	13,600d/e
F-350 4WD	5.4 V-8	7,700d
F-350 4WD	5.4 V-8	9,200e
F-350 4WD	6.8 V-10	10,500d
F-350 4WD	6.8 V-10	14,000j
F-350 4WD	7.3 V-8 TD	13,500d
F-350 4WD DRW	5.4 V-8	7,400d
F-350 4WD DRW	5.4 V-8	8,900e
F-350 4WD DRW	6.8 V-10	10,200d
F-350 4WD DRW	6.8 V-10	13,700j
F-350 4WD DRW	7.3 V-8 TD	13,100d/e
F-350 SuperCab	5.4 V-8	7,800d
F-350 SuperCab	5.4 V-8	9,300e
F-350 SuperCab	6.8 V-10	10,600d
F-350 SuperCab	6.8 V-10	14,100j
F-350 SuperCab	7.3 V-8 TD	13,600d
F-350 SuperCab DRW	5.4 V-8	7,500d
F-350 SuperCab DRW	5.4 V-8	9,000e
F-350 SuperCab DRW	6.8 V-10	10,300d
F-350 SuperCab DRW	6.8 V-10	13,800j
F-350 SuperCab DRW	7.3 V-8 TD	13,300d/e
F-350 SuperCab 4WD	5.4 V-8	7,400d
F-350 SuperCab 4WD	5.4 V-8	8,900e
F-350 SuperCab 4WD	6.8 V-10	10,200d
F-350 SuperCab 4WD	6.8 V-10	13,700j
F-350 SuperCab 4WD	7.3 V-8 TD	13,200d
F-350 SuperCab 4WD DRW	5.4 V-8	7,200d
F-350 SuperCab 4WD DRW	5.4 V-8	8,700e
F-350 SuperCab 4WD DRW	6.8 V-10	10,000d
F-350 SuperCab 4WD DRW	6.8 V-10	13,500j
F-350 SuperCab 4WD DRW	7.3 V-8 TD	12,900d/e
F-350 Crew Cab	5.4 V-8	7,500d
F-350 Crew Cab	5.4 V-8	9,000e
F-350 Crew Cab	6.8 V-10	10,300d
F-350 Crew Cab	6.8 V-10	13,800j
F-350 Crew Cab	7.3 V-8 TD	13,300d
F-350 Crew Cab DRW	6.8 V-10	10,000d
F-350 Crew Cab DRW	6.8 V-10	13,500j
F-350 Crew Cab DRW	7.3 V-8 TD	12,900d/e
F-350 Crew Cab 4WD	5.4 V-8	7,100d
F-350 Crew Cab 4WD	5.4 V-8	8,600e
F-350 Crew Cab 4WD	6.8 V-10	10,000d

F-350 Crew Cab 4WD	6.8 V-10	13,500j
F-350 Crew Cab 4WD	7.3 V-8 TD	13,000d
F-350 Crew Cab 4WD DRW	6.8 V-10	9,600d
F-350 Crew Cab 4WD DRW	6.8 V-10	13,100j
F-350 Crew Cab 4WD DRW	7.3 V-8 TD	12,600d/e
<i>Super Duty F-250/F-350,</i>		
<i>Automatic Transmission, Fifth-Wheel Towing</i>		
F-250	5.4 V-8	8,100d
F-250	5.4 V-8	9,600e
F-250	6.8 V-10	11,500d
F-250	6.8 V-10	14,500j
F-250	7.3 V-8 TD	14,000d
F-250 4WD	5.4 V-8	7,600d
F-250 4WD	5.4 V-8	9,100e
F-250 4WD	6.8 V-10	11,000d
F-250 4WD	6.8 V-10	14,000j
F-250 4WD	7.3 V-8 TD	13,500d
F-250 SuperCab	5.4 V-8	7,700d
F-250 SuperCab	5.4 V-8	9,200e
F-250 SuperCab	6.8 V-10	11,100d
F-250 SuperCab	6.8 V-10	14,100j
F-250 SuperCab	7.3 V-8 TD	13,700d
F-250 SuperCab 4WD	5.4 V-8	7,300d
F-250 SuperCab 4WD	5.4 V-8	8,800e
F-250 SuperCab 4WD	6.8 V-10	10,700d
F-250 SuperCab 4WD	6.8 V-10	13,700j
F-250 SuperCab 4WD	7.3 V-8 TD	13,200d
F-250 Crew Cab	5.4 V-8	7,400d
F-250 Crew Cab	5.4 V-8	8,900e
F-250 Crew Cab	6.8 V-10	10,800d
F-250 Crew Cab	6.8 V-10	13,800j
F-250 Crew Cab	7.3 V-8 TD	13,400d
F-250 Crew Cab 4WD	5.4 V-8	7,100d
F-250 Crew Cab 4WD	5.4 V-8	8,600e
F-250 Crew Cab 4WD	6.8 V-10	10,400d
F-250 Crew Cab 4WD	6.8 V-10	13,400j
F-250 Crew Cab 4WD	7.3 V-8 TD	13,000d
F-350	5.4 V-8	8,000d
F-350	5.4 V-8	9,500e
F-350	6.8 V-10	11,400d
F-350	6.8 V-10	14,400j
F-350	7.3 V-8 TD	13,900d
F-350 DRW	5.4 V-8	7,800d
F-350 DRW	5.4 V-8	9,300e
F-350 DRW	6.8 V-10	11,100d
F-350 DRW	6.8 V-10	14,100j
F-350 DRW	7.3 V-8 TD	13,600d/e
F-350 4WD	5.4 V-8	7,600d
F-350 4WD	5.4 V-8	9,100e
F-350 4WD	6.8 V-10	11,000d
F-350 4WD	6.8 V-10	14,000j
F-350 4WD	7.3 V-8 TD	13,500d
F-350 4WD DRW	5.4 V-8	7,300d
F-350 4WD DRW	5.4 V-8	8,800e
F-350 4WD DRW	6.8 V-10	10,600d
F-350 4WD DRW	6.8 V-10	13,600j
F-350 4WD DRW	7.3 V-8 TD	13,200d/e
F-350 SuperCab	5.4 V-8	7,700d
F-350 SuperCab	5.4 V-8	9,200e
F-350 SuperCab	6.8 V-10	11,100d
F-350 SuperCab	6.8 V-10	14,100j
F-350 SuperCab	7.3 V-8 TD	13,600d
F-350 SuperCab DRW	5.4 V-8	7,500d
F-350 SuperCab DRW	5.4 V-8	9,000e
F-350 SuperCab DRW	6.8 V-10	10,800d
F-350 SuperCab DRW	6.8 V-10	13,800j
F-350 SuperCab DRW	7.3 V-8 TD	13,400d/e
F-350 SuperCab 4WD	5.4 V-8	7,300d
F-350 SuperCab 4WD	5.4 V-8	8,800e
F-350 SuperCab 4WD	6.8 V-10	10,700d
F-350 SuperCab 4WD	6.8 V-10	13,700j
F-350 SuperCab 4WD	7.3 V-8 TD	13,300d
F-350 SuperCab 4WD DRW	5.4 V-8	7,100d
F-350 SuperCab 4WD DRW	5.4 V-8	8,600e
F-350 SuperCab 4WD DRW	6.8 V-10	10,400d
F-350 SuperCab 4WD DRW	6.8 V-10	13,400j
F-350 SuperCab 4WD DRW	7.3 V-8 TD	13,000d/e
F-350 Crew Cab	5.4 V-8	7,400d
F-350 Crew Cab	5.4 V-8	8,900e
F-350 Crew Cab	6.8 V-10	10,800d
F-350 Crew Cab	6.8 V-10	13,800j
F-350 Crew Cab	7.3 V-8 TD	13,300d
F-350 Crew Cab DRW	6.8 V-10	10,500d
F-350 Crew Cab DRW	6.8 V-10	13,500j
F-350 Crew Cab DRW	7.3 V-8 TD	13,000d/e
F-350 Crew Cab 4WD	5.4 V-8	7,100d
F-350 Crew Cab 4WD	5.4 V-8	8,600e

F-350 Crew Cab 4WD	6.8 V-10	10,400d
F-350 Crew Cab 4WD	6.8 V-10	13,400j
F-350 Crew Cab 4WD	7.3 V-8 TD	13,000d
F-350 Crew Cab 4WD DRW	6.8 V-10	10,000d
F-350 Crew Cab 4WD DRW	6.8 V-10	13,000j
F-350 Crew Cab 4WD DRW	7.3 V-8 TD	12,600d/e
<i>Super Duty F-350/450/550 Chassis Cab,</i>		
<i>Manual Transmission, Fifth-Wheel Towing</i>		
<i>(trailer weights shown assume 1,000 pounds</i>		
<i>second-unit body weight)</i>		
F-350	5.4 V-8	7,400d
F-350	5.4 V-8	8,900e
F-350	6.8 V-10	10,200d
F-350	7.3 V-8 TD	13,200d
F-350 DRW	5.4 V-8	7,000d
F-350 DRW	5.4 V-8	8,500e
F-350 DRW	6.8 V-10	9,800d
F-350 DRW	6.8 V-10	13,300j
F-350 DRW	7.3 V-8 TD	12,800d/e
F-350 4WD	5.4 V-8	7,000d
F-350 4WD	5.4 V-8	8,500e
F-350 4WD	6.8 V-10	9,900d
F-350 4WD	7.3 V-8 TD	12,800d
F-350 4WD DRW	5.4 V-8	6,600d
F-350 4WD DRW	5.4 V-8	8,100e
F-350 4WD DRW	6.8 V-10	9,400d
F-350 4WD DRW	6.8 V-10	12,900j
F-350 4WD DRW	7.3 V-8 TD	12,300d/e
F-350 SCC	5.4 V-8	7,100d
F-350 SCC	5.4 V-8	8,600e
F-350 SCC	6.8 V-10	10,000d
F-350 SCC	7.3 V-8 TD	12,900d
F-350 SCC DRW	6.8 V-10	9,600d
F-350 SCC DRW	6.8 V-10	13,100j
F-350 SCC DRW	7.3 V-8 TD	12,600d/e
F-350 SCC 4WD	5.4 V-8	6,700d
F-350 SCC 4WD	5.4 V-8	8,200e
F-350 SCC 4WD	6.8 V-10	9,600d
F-350 SCC 4WD	7.3 V-8 TD	12,500d
F-350 SCC 4WD DRW	6.8 V-10	9,200d
F-350 SCC 4WD DRW	6.8 V-10	12,700j
F-350 SCC 4WD DRW	7.3 V-8 TD	12,200d/e
F-350 CCC	5.4 V-8	6,800d
F-350 CCC	5.4 V-8	8,300e
F-350 CCC	6.8 V-10	9,700d
F-350 CCC	7.3 V-8 TD	12,700d
F-350 CCC DRW	6.8 V-10	9,300d
F-350 CCC DRW	6.8 V-10	12,800j
F-350 CCC DRW	7.3 V-8 TD	12,300d/e
F-350 CCC 4WD	5.4 V-8	6,400d
F-350 CCC 4WD	5.4 V-8	7,900e
F-350 CCC 4WD	6.8 V-10	9,300d
F-350 CCC 4WD	7.3 V-8 TD	12,200d
F-350 CCC 4WD DRW	6.8 V-10	8,900d
F-350 CCC 4WD DRW	6.8 V-10	12,400j
F-350 CCC 4WD DRW	7.3 V-8 TD	11,900d/e
F-450 DRW	6.8 V-10	14,700k/l
F-450 DRW	7.3 V-8 TD	18,200k
F-450 4WD DRW	6.8 V-10	14,400k/l
F-450 4WD DRW	7.3 V-8 TD	17,900k
F-450 CCC DRW	6.8 V-10	14,200k/l
F-450 CCC DRW	7.3 V-8 TD	17,600k
F-450 CCC 4WD DRW	6.8 V-10	13,800k,l
F-450 CCC 4WD DRW	7.3 V-8 TD	17,300k
F-550 DRW	7.3 V-8 TD	18,100k
F-550 4WD DRW	7.3 V-8 TD	17,800k
F-550 CCC DRW	7.3 V-8 TD	17,500k
F-550 CCC 4WD DRW	7.3 V-8 TD	17,200k
<i>F-350/F-450/F-550 Super Duty,</i>		
<i>Automatic Transmission, Fifth-Wheel Towing</i>		
F-350	5.4 V-8	7,400d
F-350	5.4 V-8	8,900e
F-350	6.8 V-10	10,700d
F-350	7.3 V-8 TD	13,300d
F-350 DRW	5.4 V-8	6,900d
F-350 DRW	5.4 V-8	8,400e
F-350 DRW	6.8 V-10	10,200d
F-350 DRW	6.8 V-10	13,200j
F-350 DRW	7.3 V-8 TD	12,800d/e
F-350 4WD	5.4 V-8	6,900d
F-350 4WD	5.4 V-8	8,400e
F-350 4WD	6.8 V-10	10,300d
F-350 4WD	7.3 V-8 TD	12,900d
F-350 4WD DRW	5.4 V-8	6,500d
F-350 4WD DRW	5.4 V-8	8,000e
F-350 4WD DRW	6.8 V-10	9,800d
F-350 4WD DRW	6.8 V-10	12,800j

F-350 4WD DRW	7.3 V-8 TD	12,400d/e
F-350 SCC	5.4 V-8	7,100d
F-350 SCC	5.4 V-8	8,600e
F-350 SCC	6.8 V-10	10,400d
F-350 SCC	7.3 V-8 TD	13,000d
F-350 SCC DRW	6.8 V-10	10,000d
F-350 SCC DRW	6.8 V-10	13,000j
F-350 SCC DRW	7.3 V-8 TD	12,600d/e
F-350 SCC 4WD	5.4 V-8	6,700d
F-350 SCC 4WD	5.4 V-8	8,200e
F-350 SCC 4WD	6.8 V-10	10,000d
F-350 SCC 4WD	7.3 V-8 TD	12,600d
F-350 SCC 4WD DRW	6.8 V-10	9,700d
F-350 SCC 4WD DRW	6.8 V-10	12,700j
F-350 SCC 4WD DRW	7.3 V-8 TD	12,200d/e
F-350 CCC	5.4 V-8	6,800d
F-350 CCC	5.4 V-8	8,300e
F-350 CCC	6.8 V-10	10,100d
F-350 CCC	7.3 V-8 TD	12,700d
F-350 CCC DRW	6.8 V-10	9,800d
F-350 CCC DRW	6.8 V-10	12,800j
F-350 CCC DRW	7.3 V-8 TD	12,300d/e
F-350 CCC 4WD	5.4 V-8	6,400d
F-350 CCC 4WD	5.4 V-8	7,900e
F-350 CCC 4WD	6.8 V-10	9,700d
F-350 CCC 4WD	7.3 V-8 TD	12,300d
F-350 CCC 4WD DRW	6.8 V-10	9,400d
F-350 CCC 4WD DRW	6.8 V-10	12,400j
F-350 CCC 4WD DRW	7.3 V-8 TD	11,900d/e
F-450 DRW	6.8 V-10	16,700k
F-450 DRW	6.8 V-10	18,700l
F-450 DRW	7.3 V-8 TD	18,200k
F-450 4WD DRW	6.8 V-10	16,400k
F-450 4WD DRW	6.8 V-10	18,400l
F-450 4WD DRW	7.3 V-8 TD	17,900k
F-450 CCC DRW	6.8 V-10	16,100k
F-450 CCC DRW	6.8 V-10	18,100l
F-450 CCC DRW	7.3 V-8 TD	17,600k
F-450 CCC 4WD DRW	6.8 V-10	15,800k
F-450 CCC 4WD DRW	6.8 V-10	17,800l
F-450 CCC 4WD DRW	7.3 V-8 TD	17,300k
F-550 DRW	6.8 V-10	16,600k
F-550 DRW	6.8 V-10	18,600l
F-550 DRW	7.3 V-8 TD	18,100k
F-550 DRW	7.3 V-8 TD	22,100l
F-550 4WD DRW	6.8 V-10	16,300k
F-550 4WD DRW	6.8 V-10	18,300l
F-550 4WD DRW	7.3 V-8 TD	17,800k
F-550 4WD DRW	7.3 V-8 TD	21,800l
F-550 CCC DRW	6.8 V-10	16,000k
F-550 CCC DRW	6.8 V-10	18,000l
F-550 CCC DRW	7.3 V-8 TD	17,600k
F-550 CCC DRW	7.3 V-8 TD	21,600l
F-550 CCC 4WD DRW	6.8 V-10	15,700k
F-550 CCC 4WD DRW	6.8 V-10	17,700l
F-550 CCC 4WD DRW	7.3 V-8 TD	17,200k
F-550 CCC 4WD DRW	7.3 V-8 TD	21,200l

Super Duty F-650/F-750

F-650 all models	All	40,000 gcwr*
F-750 all models	All	45,000/60,000 gcwr*

* To determine maximum trailer weight, subtract vehicle gvwr from the maximum gcwr.

Ranger, Automatic Transmission

Ranger	2.3 I-4	2,295e*
Ranger	2.5 I-4	2,195e
Ranger	3.0 V-6	4,145d/4,010d**
Ranger	4.0 V-6	6,070c/5,940c**
Ranger 4WD	3.0 V-6	3,895d/e
Ranger 4WD	4.0 V-6	5,820d/e
Ranger SuperCab	3.0 V-6	3,955d/3,825d**
Ranger SuperCab	4.0 V-6	5,885c/5,755c**
Ranger SuperCab 4WD	3.0 V-6	3,700d/e
Ranger SuperCab 4WD	4.0 V-6	5,620d/e

Ranger, Manual Transmission

Ranger	3.0 V-6	2,685d/2,550d**
Ranger	4.0 V-6	3,610c/3,480c**
Ranger 4WD	3.0 V-6	2,430d/e
Ranger 4WD	4.0 V-6	3,360d/e
Ranger SuperCab	3.0 V-6	2,495d/2,365d**
Ranger SuperCab	4.0 V-6	3,420c/3,285c**
Ranger SuperCab 4WD	3.0 V-6	2,230d/e
Ranger SuperCab 4WD	4.0 V-6	3,155d/e

*Late availability; **Ranger Edge only

Windstar

Windstar Wagon	3.8 V-6	2,000
Winstar Van	3.8 V-6	2,000
Windstar Wagon	3.8 V-6	3,500f

TD = Turbodiesel Ext = Extended Cab
 NGV = Natural Gas Vehicle DRW = Dual-rear Wheels
 SCC = Super Chassis Cab CCC = Crew Chassis Cab

- a = Requires 3.08:1 axle ratio
- b = Requires 3.31:1 axle ratio
- c = Requires 3.55:1 axle ratio
- d = Requires 3.73:1 axle ratio;
- e = Requires 4.09/4.10:1 axle ratio
- f = Must be equipped with heavy-duty towing package
- g = Requires 16- or 17-inch (P275) wheel option
- h = Requires 17-inch (P265) wheel option
- i = Requires 3.27:1 axle ratio
- j = Requires 4.30:1 axle ratio
- k = Requires 4.88:1 axle ratio;
- l = Requires 5.38:1 axle ratio
- m = Available in high-altitude areas only
- n = With Class II trailer towing package. Rating is 2,000 without.

HONDA

Vehicle	Engine	Tow Limit (lbs)
Odyssey	V-6 24-valve	3,500a,b
Passport	3.2 V-6	4,500c

- a = With transmission fluid cooler and two occupants.
- Deduct 150 pounds per passenger up to seven passengers
- b = Without transmission cooler: 2,000 pounds maximum with two occupants
- c = Requires load-leveling hitch.

HYUNDAI

Vehicle	Engine	Tow Limit (lbs)
Santa Fe	2.4 I-4	2,000
Santa Fe	2.7 V-6	2,700
Sonata	2.5 V-6	2,000a

- a = Trailer must have brakes (without brakes = 1,000 pounds).

INFINITI

Vehicle	Engine	Tow Limit (lbs)
QX4	3.5 V-6	5,000

ISUZU

Vehicle	Engine	Tow Limit (lbs)
Axiom*	3.5 V-6	4,500a
Rodeo/Rodeo Sport	2.2/2.6 I-4	2,500
Rodeo/Rodeo Sport	3.2 V-6	4,500a
Trooper	3.5 V-6	5,000a

- *2002 model, available spring 2001
- a = trailer brakes required on any trailer heavier than 3,500 pounds.

JAGUAR

Vehicle	Engine	Tow Limit (lbs)
XJ	4.0 V-8	3,307

JEEP

Vehicle	Engine	Tow Limit (lbs)
Wrangler	2.5 I-4/4.0 I-6	2,000a,f
Cherokee/Grand Cherokee	4.0 I-6	5,000b,c,d
Grand Cherokee Limited (4WD)	4.0 I-6	5,000b
Grand Cherokee	4.7 V-8	6,500b,c,d,e

Note: Trailer brakes required on all trailers weighing more than 1,000 pounds.

- a = Wrangler rating is 1,000 pounds with automatic transmission
- b = Requires weight-distributing hitch with a maximum hitch weight of 750 pounds
- c = Requires trailer-towing package
- d = Requires automatic transmission
- e = 4WD rated 200 pounds lower
- f = Maximum hitch weight of 300 pounds

KIA

Vehicle	Engine	Tow Limit (lbs)
Spportage all models	2.0 I-4	2,000

LAND ROVER

Vehicle	Engine	Tow Limit (lbs)
Discovery, Series II	All	5,500a,b
Range Rover	All	6,500a,b

- a = Maximum trailer weight without brakes is 1,650 pounds
- b = Off-road maximum is 2,200 pounds.

LEXUS

Vehicle	Engine	Tow Limit (lbs)
LX 470	4.7 V-8	6,500
RX 300	3.0 V-6	3,500
LS 430	4.3 V-8	2,000
ES 300	3.0 V-6	2,000

LINCOLN

Vehicle	Engine	Tow Limit (lbs)
Town Car & LS	4.6 V-8	2,000
Navigator	5.4 V-8	8,800a,b

- a = Requires optional Class III/IV Trailer Tow Package with load-equalizing hitch
- b = 4WD tow rating is 8,000 pounds.

MAZDA

Vehicle	Engine	Tow Limit (lbs)
B2500	2.5 I-4	2,240a,e
B3000	3.0 V-6	4,000a,d,e
B3000 4WD	3.0 V-6	4,360a,d,e
B4000	4.0 V-6	5,900a,c,d,e
B4000 4WD	4.0 V-6	5,700a,c,d
MPV	2.5 V-6	3,000b
Tribute	3.0 V-6	3,500b

- a = Requires automatic transmission; rating lower with manual transmission
- b = Requires trailer-towing package
- c = Requires special axle ratio and trailer-towing package
- d = Requires load-equalizing hitch for more than 2,000 pounds
- e = Cab Plus rating lower.

MERCEDES-BENZ

Vehicle	Engine	Tow Limit (lbs)
ML 320	3.2 V-6	5,000
ML 430	4.3 V-8	5,000
ML55 AMG	5.5 V-8	5,000

MERCURY

Vehicle	Engine	Tow Limit (lbs)
Grand Marquis	4.6 V-8	2,000a
Mountaineer 2WD	4.0 V-6	5,900c
Mountaineer 4WD	4.0 V-6	5,700c
Mountaineer 2WD	5.0 V-8	6,760
Mountaineer AWD	5.0 V-8	6,560
Villager	3.3 V-6	2,000a
Villager	3.3 V-6	3,500b

- a = Class I load-carrying type/weight-equalizing hitch
- b = Requires optional Class II towing package
- c = Requires Class IV load-equalizing hitch option and 3.73:1 gear ratio (standard on V-8)

MINI

Vehicle	Engine	Tow Limit (lbs)
Montero ES, LS, XLS	3.0 V-6	5,000a
Montero Limited, 3.5 XS	3.5 V-6	5,000a

- a = Tow rating with trailer brakes; 1,500 pounds maximum rating without

NISSAN

Vehicle	Engine	Tow Limit (lbs)
Frontier	2.4 I-4	3,500b,c
Frontier	3.3 V-6	5,000a
Pathfinder	3.5 V-6	5,000a
Quest	3.3 V-6	3,500
Xterra	2.4 I-4	3,500

Xterra	3.3 V-6	5,000a
--------	---------	--------

- a = Rating is 3,500 pounds with manual transmission
- b = Requires manual transmission
- c = Rating is 2,000 pounds with an automatic transmission.
- *Tow limit on supercharged V-6-equipped Frontier not available at presstime.

OLDSMOBILE

Vehicle	Engine	Tow Limit (lbs)
Bravada	4.3 V-6	5,000a
Silhouette	3.4 V-6	3,500b

- a = Weight-distributing platform hitch recommended when exceeding 3,500 pounds
- b = Requires towing package.

PONTIAC

Vehicle	Engine	Tow Limit (lbs)
Aztec	3.4 V-6	3,500a
Montana	3.4 V-6	3,500a

- a = Requires towing package.

SAAB

Vehicle	Engine	Tow Limit (lbs)
All	All	3,500a

- a = Maximum trailer weight without brakes is 1,000 pounds.

SUBARU

Vehicle	Engine	Tow Limit (lbs)
Legacy/Outback/Forester	2.5 SOHC I-42,000a	

- a = Trailer brakes required. Maximum hitch weight 200 pounds.

TOYOTA

Vehicle	Engine	Tow Limit (lbs)
4Runner	3.4 V-6	5,000
Camry/Avalon	all	2,000
Land Cruiser	4.7 V-8	6,500
Sequoia	4.7 V-8	6,500
Sequoia 4WD	4.7 V-8	6,200
Sienna	3.0 V-6	3,500
S-Runner	3.4 V-6	3,500
Tacoma	All I-4	3,500
Tacoma	3.4 V-6	5,000
Tundra 2WD B-Cab	3.4 V-6 M	5,250
Tundra 2WD B-Cab	3.4 V-6 A	5,200
Tundra 2WD C-Cab	3.4 V-6 M	4,950
Tundra 2WD C-Cab	3.4 V-6 A	4,900
Tundra 4WD C-Cab	3.4 V-6 M	5,000
Tundra 4WD C-Cab	3.4 V-6 A	4,950
Tundra 2WD C-Cab (SR5, LTD)	4.7 V-8	7,200
Tundra 4WD B-Cab	4.7 V-8	7,200
Tundra 4WD C-Cab (SR5, LTD)	4.7 V-8	7,100

- M= Manual transmission A= Automatic transmission
- 2WD = 2-wheel drive 4WD = 4-wheel drive.
- All vehicles' tongue weight is 10 percent of maximum towing capacity. Sienna's (CE and LE) 3,500-pound maximum is achieved with an optional towing package

VOLKSWAGEN

Vehicle	Engine	Tow Limit (lbs)
Eurovan	2.8 V-6	4,400a

- a = With trailer brakes. Limit for trailer without brakes is 2,200 pounds.

VOLVO

Vehicle	Engine	Tow Limit (lbs)
All, except S40 & V40	All	3,300a
S40 & V40	All	2,000a

- a = Volvo hitch is recommended. When towing trailers more than 1,540 pounds, brakes are required.